

REVISED VERSION

(19) World Intellectual Property
Organization
International Bureau



22 SEP 2004

(43) International Publication Date
9 October 2003 (09.10.2003)

PCT

(10) International Publication Number
WO 2003/082407 A1

(51) International Patent Classification⁷: A62C 39/00, 5/00

City Gate, 95-107 Southampton Street, Reading, Berkshire
RG1 2QW (GB).

(21) International Application Number:

PCT/GB2003/001394

(22) International Filing Date: 28 March 2003 (28.03.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0207466.4

28 March 2002 (28.03.2002) GB

(71) Applicant (for all designated States except US): **KIDDE
IP HOLDINGS LIMITED** [GB/GB]; Mathisen Way,
Colnbrook, Slough SL3 0HB (GB).


(74) Agent: **MATHISEN & MACARA**; The Coach House,
6-8 Swakeleys Road, Ickenham, Uxbridge UB10 8BZ
(GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: FIRE AND EXPLOSION SUPPRESSION



(57) Abstract: A fire and explosion suppression system comprises a source (5) of high pressure water which is fed to a misting nozzle (13) at one input of a mixing unit (6), and a source (14) of high pressure inert gas, such as nitrogen, which is fed along a pipe (20) to another input of the mixing unit (6). Inside the mixing unit (6), water mist, in the form of an atomised mist of very small droplet size is mixed with the pressurised gas and exits the mixing unit (6) at high pressure and high velocity along a pipe (22) and is then discharged through spreaders (26, 28). The source (5) of the water is pressurised by a feed (30) from the source of pressurised inert gas. The mass flow rate of the water will therefore reduce as the pressure of the gas decays. This tends to maintain the ratio of the mass flow rate of the water to the mass flow rate of the gas constant. This is found to produce and maintain an advantageous distribution of droplet size in the discharged mist. A control unit (10) adjusts a metering valve (7) in dependence on the mass flow rate or the pressure of the gas in order to adjust the ratio as necessary to maintain its value constant.

WO 2003/082407 A1